



CONSTELLATION OVERVIEW

Suomi NPP (NASA/NOAA)








NOAA 18/19 (NOAA)

(JAXA)





SPACECRAFT OVERVIEW











MISSION OVERVIEW

- Advancing precipitation measurement capability from space
- Improving knowledge of precipitation systems, water cycle variability, and fresh water availability
- Improving climate modeling and prediction
- Improving weather predication and 4-D climate reanalysis
- Improving hydrometeorological modeling and prediction




Image credit: NASA/JAXA, Hal Pierce








INTEGRATED MULTI-SATELLITE RETRIEVALS FOR GPM (IMERG) SCIENCE PRODUCT







PRECIPITATION PROCESSING SYSTEM (PPS) SCIENCE PRODUCT





















COMMAND AND DATA HANDLING OVERVIEW





- 36 MB SRAM
- 8 MB SRAM for SpaceWire
- 4 MB EEPROM
- SpaceWire router
- MIL-STD-1553










- EEPROM File System (EEFS)
 - Core Flight Executive (cFE) Startup Scripts
 - Uncompressed cFE Object Files
 - Default FSW Binary Table Files
 - Compressed Application Object Files
 - Libraries for all GPM FSW applications

- Local SRAM
 - All applications and tables





COMMAND AND DATA HANDLING OVERVIEW











SBC INITIALIZATION TYPES


Reset Type	Reset Subtype	Cause
	Power cycle	Power having been removed and restored
	Command	cFE processing a reset command
Power On	HW debug	Debug mode connection
	Bank switch	Reset reverted to a cFE power on
		due to a bank switch
	Undefined	Unknown reset type
Processor	HW watchdog	Watchdog timer expiring
	Exception	Processor exception
	Command	cFE processing a reset command







CCSDS FILE DELIVERY PROTOCOL







DIFFERENCE BETWEEN TRADITIONAL METHOD AND PERP









FILE COMMANDING (FC) APPLICATION

The key to the PERP.







GPM — POR EXPEDITED RECOVERY PROCESS DESIGN FILE COMMANDING (FC) APPLICATION



- Interfaces with the cFE environment
- Processes ground-uplinked binary files
 - Reads command packets
 - Routes commands to the appropriate receiver application
- Processes five commands per second at max, one command per sixty seconds at min
- Allows for long commands otherwise not accepted by the ground system
- Unlimited queue with optional specified delay parameters








- 1. Identify required loads and order in which to repopulate RAM.
- 2. Build procedure that performs the RAM reloading based on Step 1.
- 3. Run procedure from Step 2 on GPM Simulator.
- 4. Capture the commands sent to simulator and compile them.
- 5. Create FC file from the compiled commands.
- 6. Compress FC file.







RECOVERY PROCESS — LOAD UPLINK











RECOVERY PROCESS – WBS HOURLY COMPARISON

Activity	Traditional Estimate	PERP Estimate
Initial anomaly assessment	2	2
Scheduling of supports	8	2
Planning of RAM reload	3	1
CAM to reload RAM	3	1
Execution of RAM reload	40	2
FOT support required	720	72
Post-anomaly support	4	4
Total	780	84





